

## Safety Data Sheet

### MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 1/11  
(30605798/SDS\_GEN\_US/EN)

#### 1. Identification

**Product identifier used on the label**

**MasterProtect HB 300SB medium also SUPER COL  
C VOC FIN MEDIUM**

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: Coating

---

#### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

|                       |                        |   |
|-----------------------|------------------------|---|
| Flam. Liq.<br>STOT RE | 4<br>1 (by inhalation) | Flammable liquids<br>Specific target organ toxicity — repeated exposure |
| Aquatic Acute         | 3                      | Hazardous to the aquatic environment - acute                            |
| Aquatic Chronic       | 3                      | Hazardous to the aquatic environment - chronic                          |

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 2/11  
(30605798/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

|      |   |
|------|---|
| H227 | Combustible liquid.   |
| H372 | Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation). |
| H402 | Harmful to aquatic life.  |
| H412 | Harmful to aquatic life with long lasting effects.                                  |

Precautionary Statements (Prevention):

|      |  |
|------|--|
| P260 | Do not breathe dust/gas/mist/vapours.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P280 | Wear protective gloves and eye/face protection.  |
| P273 | Avoid release to the environment.  |
| P270 | Do not eat, drink or smoke when using this product.  |
| P264 | Wash with plenty of water and soap thoroughly after handling.                                  |

Precautionary Statements (Response):

|             |  |
|-------------|--|
| P314        | Get medical advice/attention if you feel unwell.                                     |
| P370 + P378 | In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction. |

Precautionary Statements (Storage):

|             |  |
|-------------|--|
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
|-------------|--|

Precautionary Statements (Disposal):

|      |   |
|------|---|
| P501 | Dispose of contents/container to hazardous or special waste collection point. |
|------|---|

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

**According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

### Emergency overview

WARNING:  
COMBUSTIBLE LIQUID.  
MAY CAUSE EYE IRRITATION.  
MAY CAUSE SKIN IRRITATION.  
CONTAINS MATERIAL WHICH CAN CAUSE CANCER.  
Avoid contact with the skin, eyes and clothing.  
Wash thoroughly after handling.  
Keep container tightly closed.

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 3/11  
(30605798/SDS\_GEN\_US/EN)

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| <u>CAS Number</u> | <u>Content (W/W)</u> | <u>Chemical name</u>                    |
|-------------------|----------------------|---|
| 1317-65-3         | >= 15.0 - < 25.0 %   | Limestone                               |
| 14808-60-7        | >= 15.0 - < 20.0 %   | crystalline silica                      |
| 13463-67-7        | >= 7.0 - < 10.0 %    | Titanium dioxide                        |
| 64742-49-0        | >= 3.0 - < 5.0 %     | Naphtha (petroleum), hydrotreated light |
| 26530-20-1        | >= 0.0 - < 0.1 %     | 2-octyl-4-isothiazol-3-ones             |

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

| <u>CAS Number</u> | <u>Content (W/W)</u> | <u>Chemical name</u>                    |
|-------------------|----------------------|---|
| 1317-65-3         | >= 15.0 - < 25.0 %   | Limestone                               |
| 14808-60-7        | >= 15.0 - < 20.0 %   | crystalline silica                      |
| 13463-67-7        | >= 7.0 - < 10.0 %    | Titanium dioxide                        |
| 64742-49-0        | >= 3.0 - < 5.0 %     | Naphtha (petroleum), hydrotreated light |
| 26530-20-1        | >= 0.0 - < 0.1 %     | 2-octyl-4-isothiazol-3-ones             |

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

#### Indication of any immediate medical attention and special treatment needed

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 4/11  
(30605798/SDS\_GEN\_US/EN)

---

### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.  
For large amounts: Pump off product.

---

## 7. Handling and Storage

### Precautions for safe handling

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 5/11  
(30605798/SDS\_GEN\_US/EN)

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 5 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 40 °F

The packed product must be protected from temperatures below the indicated one.

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

|                    |           |   |
|--------------------|-----------|---|
| Limestone          | OSHA PEL  | PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;   |
| Titanium dioxide   | OSHA PEL  | PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;   |
|                    | ACGIH TLV | TWA value 10 mg/m3 ;  |
| crystalline silica | OSHA PEL  | TWA value 2.4 millions of particles per cubic foot of air Respirable ;<br>The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.<br>TWA value 0.1 mg/m3 Respirable ;<br>The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.<br>TWA value 0.3 mg/m3 Total dust ;<br>The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. |
|                    | ACGIH TLV | TWA value 0.025 mg/m3 Respirable fraction ;   |

### Advice on system design:

No applicable information available.

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 6/11  
(30605798/SDS\_GEN\_US/EN)

### Personal protective equipment

#### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

#### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

#### **Eye protection:**

Safety glasses with side-shields.

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

#### **General safety and hygiene measures:**

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

|   |   |                                      |
|---|---|--------------------------------------|
| Form:   | liquid  |                                      |
| Odour:  | solvent-like, slight odour  |                                      |
| Odour threshold:                                    |   | No applicable information available. |
| Colour:   | various colours   |                                      |
| pH value:   |   | neutral to slightly alkaline         |
| Melting point:                                      |   | No applicable information available. |
| Boiling point:                                      | 65.56 - 228.89<br>°C  |                                      |
| Sublimation point:                                  |   | No applicable information available. |
| Flash point:  | 87.78 °C  |                                      |
| Flammability:                                       | not determined  |                                      |
| Lower explosion limit:                              | 0.6 %(V)  |                                      |
| Upper explosion limit:                              | 20.4 %(V)   |                                      |
| Vapour pressure:                                    |   | No data available.                   |
| Density:  | 1 g/cm <sup>3</sup>   | ( 20 °C)                             |
| Relative density:                                   | 1   |                                      |
| Bulk density:                                       |   | not applicable                       |
| Vapour density:                                     |   | Heavier than air.                    |
| Partitioning coefficient n-octanol/water (log Pow): |   | No data available.                   |
| Thermal decomposition:                              | No decomposition if stored and handled as prescribed/indicated.                                   |                                      |
| Viscosity, dynamic:                                 |   | No applicable information available. |
| Viscosity, kinematic:                               |   | No applicable information available. |
| Solubility in water:                                |   | partly soluble                       |
| Solubility (quantitative):                          |   | No applicable information available. |
| Solubility (qualitative):                           | No applicable information available.  |                                      |
| Evaporation rate:                                   |   | No applicable information available. |
| Other Information:                                  | If necessary, information on other physical and chemical parameters is indicated in this section. |                                      |

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 7/11  
(30605798/SDS\_GEN\_US/EN)

---

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

#### Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

#### Hazardous decomposition products

#### Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

#### Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

##### Oral

No applicable information available.

##### Inhalation

No applicable information available.

##### Dermal

No applicable information available.

##### Assessment other acute effects

No applicable information available.

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 8/11  
(30605798/SDS\_GEN\_US/EN)

### Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling. Based on available Data, the classification criteria are not met.

### Sensitization

Assessment of sensitization: The product contains 2-n-octyl-4-isothiazolin-3-one (CAS-No.: 26530-20-1). The substance may cause sensitization of the skin on particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

## Chronic Toxicity/Effects

### Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### *Information on: crystalline silica*

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen. NTP listed carcinogen*

### *Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Other Information



# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 9/11  
(30605798/SDS\_GEN\_US/EN)

---

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

### Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

### Mobility in soil

Assessment transport between environmental compartments

No data available.

### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 10/11  
(30605798/SDS\_GEN\_US/EN)

---

### 14. Transport Information

**Land transport**  
USDOT

Not classified as a dangerous good under transport regulations

**Sea transport**  
IMDG

Not classified as a dangerous good under transport regulations

**Air transport**  
IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

#### Federal Regulations

**Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Acute; Chronic; Fire

#### State regulations

| <u>State RTK</u> | <u>CAS Number</u> | <u>Chemical name</u> |
|------------------|-------------------|----------------------|
| MA, NJ, PA       | 1317-65-3         | Limestone            |
| MA, NJ, PA       | 14808-60-7        | crystalline silica   |
| MA, NJ, PA       | 13463-67-7        | Titanium dioxide     |

**CA Prop. 65:**

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

**NFPA Hazard codes:**

Health : 2 Fire: 2 Reactivity: 0 Special:

**HMIS III rating**

Health: 2<sup>+</sup> Flammability: 2 Physical hazard: 0

---

### 16. Other Information

**SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2015/02/24

# Safety Data Sheet

## MasterProtect HB 300SB medium also SUPER COL C VOC FIN MEDIUM

Revision date : 2015/02/24  
Version: 2.0

Page: 11/11  
(30605798/SDS\_GEN\_US/EN)

---

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET