

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15

Page: 1/10

Version: 3.0

(30605557/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal CR 190 PART B also EPOLITH P PTB

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	1B	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Repr.	2 (fertility)	Reproductive toxicity
Repr.	2 (unborn child)	Reproductive toxicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Aquatic Acute	1	Hazardous to the aquatic environment - acute
Aquatic Chronic	1	Hazardous to the aquatic environment - chronic

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 2/10
(30605557/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility. Suspected of damaging the unborn child.
H314	Causes severe skin burns and eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P352	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P391	Collect spillage.
P362 + P364	Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 3/10
(30605557/SDS_GEN_US/EN)

Emergency overview

DANGER:
HARMFUL IF SWALLOWED.
MAY BE HARMFUL IF INHALED.
MAY CAUSE BURNS.
MAY CAUSE ALLERGIC SKIN REACTION.
Irritating to eyes, respiratory system and skin.
Contains a suspect teratogen.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.
Keep container tightly closed.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25154-52-3	>= 30.0 - <= 40.0 %	nonylphenol
112-57-2	>= 5.0 - <= 10.0 %	3,6,9-triazaundecamethylene-1,11-diamine
68082-29-1	>= 5.0 - <= 10.0 %	fatty acide aminoamides
112-24-3	< 1.0 %	triethylenetetramine
1760-24-3	< 0.5 %	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-
25154-52-3	>= 25.0 - < 50.0 %	nonylphenol
112-57-2	>= 7.0 - < 10.0 %	3,6,9-triazaundecamethylene-1,11-diamine
1760-24-3	>= 0.1 - < 0.3 %	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
68953-36-6	30.0 - 60.0 %	Fatty acids, tall-oil, reaction products with tetraethylenepentamine
25154-52-3	15.0 - 40.0 %	nonylphenol
27554-26-3	7.0 - 13.0 %	di-isooctyl phthalate
112-57-2	5.0 - 10.0 %	3,6,9-triazaundecamethylene-1,11-diamine

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 4/10
(30605557/SDS_GEN_US/EN)

If swallowed:

Do not induce vomiting. Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: skin corrosion, Eye irritation, allergic symptoms

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 5/10
(30605557/SDS_GEN_US/EN)

7. Handling and Storage

Precautions for safe handling

Keep away from sources of ignition - No smoking. Keep container tightly sealed. Handle and open container with care.

Protection against fire and explosion:

The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls/Personal Protection

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

Wear chemical resistant protective gloves., Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	mild, ammonia-like	
Odour threshold:		No applicable information available.
Colour:	black	
pH value:		neutral to slightly alkaline
boiling temperature:	approx. 112.78 °C	
Flash point:	93.34 °C	(ASTM D93)

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 6/10
(30605557/SDS_GEN_US/EN)

Flammability:	200 °F not highly flammable	
Lower explosion limit:	1 %(V)	
Upper explosion limit:	6 %(V)	
Density:	approx. 0.96 g/cm ³	(20 °C)
	approx. 7.99 lb/USg	(20 °C)
Relative density:	0.96	
Vapour density:		Heavier than air.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Solubility in water:		(15 °C) insoluble
Miscibility with water:		(15 °C) not (e.g. <10%)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

zinc, aluminium, oxidizing agents, strong alkalies, acids

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral

Type of value: ATE

Value: 1,520 mg/kg

Inhalation

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 7/10
(30605557/SDS_GEN_US/EN)

Type of value: ATE
Value: > 20.0000 mg/l
Determined for vapor

Type of value: ATE
Value: > 5.0000 mg/l
Determined for mist

Dermal

Type of value: ATE
Value: > 5,000 mg/kg

Assessment other acute effects

Assessment of STOT single:
Causes temporary irritation of the respiratory tract.

Irritation / corrosion

Assessment of irritating effects: Causes burns. Risk of serious damage to eyes. Ingestion may cause severe irritation of the gastrointestinal tract. Irritating to eyes, respiratory system and skin.

Information on: nonylphenol

Assessment of irritating effects: Corrosive! Damages skin and eyes. May cause severe damage to the eyes.

Information on: 3,6,9-triazaundecamethylene-1,11-diamine

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Can sensitize the skin and/or respiratory tract of allergic persons. May produce an allergic reaction.

Chronic Toxicity/Effects

Reproductive toxicity

Information on: nonylphenol

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Teratogenicity

Information on: nonylphenol

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Information on: di-isooctyl phthalate

Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 8/10
(30605557/SDS_GEN_US/EN)

tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

skin corrosion, Eye irritation, allergic symptoms

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Very toxic (acute effect) to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

The organic component of the product is biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested.

Very toxic (acute effect) to aquatic organisms. May cause long-term adverse effects in the aquatic environment. The product should not be allowed to reach either ground or open waters. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class: 8

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15
Version: 3.0

Page: 9/10
(30605557/SDS_GEN_US/EN)

Packing group: II
ID number: UN 3267
Hazard label: 8, EHS
Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains TRIETHYLENETETRAMINE, NONYLPHENOL)

Sea transport IMDG

Hazard class: 8
Packing group: II
ID number: UN 3267
Hazard label: 8, EHS
Marine pollutant: YES
Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains TRIETHYLENETETRAMINE, NONYLPHENOL)

Air transport IATA/ICAO

Hazard class: 8
Packing group: II
ID number: UN 3267
Hazard label: 8
Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (contains TRIETHYLENETETRAMINE, NONYLPHENOL)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	67-56-1; 107-15-3	Methanol; ethylenediamine

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	25154-52-3	nonylphenol
PA	27554-26-3	di-isooctyl phthalate
MA, NJ, PA	112-57-2	3,6,9-triazaundecamethylene-1,11-diamine

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 3 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Safety Data Sheet

MasterSeal CR 190 PART B also EPOLITH P PTB

Revision date : 2015/01/15

Page: 10/10

Version: 3.0

(30605557/SDS_GEN_US/EN)

Health: 3 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2015/01/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET