

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 1/7
(55400146/SDS_GEN_US/EN)

1. Product and Company Identification

Use: Product for construction chemicals

Company
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

2. Hazards Identification

Emergency overview

DANGER:
HARMFUL IF SWALLOWED.
MAY BE HARMFUL IF INHALED.
MAY CAUSE BURNS.
MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE ALLERGIC RESPIRATORY REACTION.
CONTAINS MATERIAL WHICH MAY CAUSE CANCER.
May cause sensitization by skin contact.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.
Keep container tightly closed.

State of matter: liquid
Odour: product specific

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

The product has not been tested. The statement has been derived from the properties of the individual components.

Irritation / corrosion:

The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization:

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 2/7
(55400146/SDS_GEN_US/EN)

May produce an allergic reaction. Sensitization after skin contact possible. The product has not been tested. The statement has been derived from the properties of the individual components.

Potential environmental effects

Aquatic toxicity:

The product has not been tested.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14807-96-6	>= 15.0 - <= 40.0 %	talc
25085-99-8	>= 15.0 - <= 40.0 %	Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer
68953-36-6	>= 10.0 - <= 30.0 %	Fatty acids, tall-oil, reaction products with tetraethylenepentamine
25154-52-3	>= 10.0 - <= 30.0 %	nonylphenol
27554-26-3	>= 7.0 - <= 13.0 %	di-isooctyl phthalate
68082-29-1	>= 5.0 - <= 10.0 %	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine
112945-52-5	>= 1.0 - <= 5.0 %	Silica
112-57-2	>= 1.0 - <= 5.0 %	3,6,9-triazaundecamethylene-1,11-diamine
13463-67-7	>= 0.5 - <= 1.5 %	Titanium dioxide

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-Fighting Measures

Flash point: > 201 °F
> 94 °C

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 3/7
(55400146/SDS_GEN_US/EN)

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

General advice:

Keep away from sources of ignition - No smoking. Keep container tightly sealed. Handle and open container with care.

Protection against fire and explosion:

The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

General advice:

Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

Titanium dioxide	OSHA	PEL 15 mg/m3 Total dust ;
	ACGIH	TWA value 10 mg/m3 ;
talc	OSHA	TWA value 20 millions of particles per cubic foot of air ;
		TWA value 2.4 millions of particles per cubic foot of air Respirable ;
		The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
		TWA value 0.1 mg/m3 Respirable ;
		The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
		TWA value 0.3 mg/m3 Total dust ;
		The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 4/7
(55400146/SDS_GEN_US/EN)

	ACGIH	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Silica	OSHA	; listed TWA value 20 millions of particles per cubic foot of air ; TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, 80/(%SiO ₂), using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

Wear chemical resistant protective gloves., Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
pH value:		neutral to slightly alkaline
Boiling point:		not applicable
Density:	approx. 1.00 g/cm ³	(20 °C)
Bulk density:		not applicable

10. Stability and Reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Substances to avoid:

zinc, aluminium, oxidizing agents, strong alkalies, acids

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 5/7
(55400146/SDS_GEN_US/EN)

No decomposition if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

11. Toxicological information

Acute toxicity

Information on: nonylphenol

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of low toxicity after short-term skin contact.

Irritation / corrosion

Information on: nonylphenol

Assessment of irritating effects:

Corrosive! Damages skin and eyes. May cause severe damage to the eyes.

Information on: 3,6,9-triazaundecamethylene-1,11-diamine

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Information on: Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer

Assessment of sensitization:

May cause sensitization by skin contact.

Can sensitize the skin and/or respiratory tract of allergic persons. May produce an allergic reaction.

Reproductive toxicity

Information on: nonylphenol

The results of animal studies suggest a fertility impairing effect.

Information on: di-isooctyl phthalate

Causes impairment of fertility in laboratory animals. The product has not been tested. The statement has been derived from products of a similar structure or composition.

Development:

Information on: nonylphenol

Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Information on: di-isooctyl phthalate

The substance caused malformations/developmental toxicity in laboratory animals. The product has not been tested. The statement has been derived from products of a similar structure or composition.

12. Ecological Information

Other adverse effects:

The product has not been tested.

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 6/7
(55400146/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class: 8
Packing group: III
ID number: UN 1760
Hazard label: 8
Proper shipping name: CORROSIVE LIQUID, N.O.S. (contains ALKYLAMINE, NONYLPHENOL)

Sea transport

IMDG

Hazard class: 8
Packing group: III
ID number: UN 1760
Hazard label: 8
Marine pollutant: NO
Proper shipping name: CORROSIVE LIQUID, N.O.S. (contains ALKYLAMINE, NONYLPHENOL)

Air transport

IATA/ICAO

Hazard class: 8
Packing group: III
ID number: UN 1760
Hazard label: 8
Proper shipping name: CORROSIVE LIQUID, N.O.S. (contains ALKYLAMINE, NONYLPHENOL)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

OSHA hazard category:

IARC 1, 2A or 2B carcinogen; Chronic target organ effects reported; OSHA PEL established; ACGIH TLV established

EPCRA 311/312 (Hazard categories):

Acute; Chronic

CERCLA RQ

CAS Number

Chemical name

Safety Data Sheet

EPOLITH G KIT

Revision date : 2011/08/31
Version: 1.0

Page: 7/7
(55400146/SDS_GEN_US/EN)

5000 LBS 67-56-1; 107-15-3 Methanol; ethylenediamine

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	14807-96-6	talc
MA, NJ, PA	25154-52-3	nonylphenol
NJ, PA	27554-26-3	di-isooctyl phthalate
MA, NJ, PA	112945-52-5	Silica
MA, NJ, PA	112-57-2	3,6,9-triazaundecamethylene-1,11-diamine
MA, NJ, PA	13463-67-7	Titanium dioxide

CA Prop. 65:
THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other Information

HMIS III rating

Health: 3 \square Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

MSDS Prepared on: 2011/08/31

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET