

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 1/9
(30605606/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

**MasterSeal M 265 PART A also CONIPUR 265Z
BASE COAT PTA**

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No applicable information available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	1	Hazardous to the aquatic environment - acute
Aquatic Chronic	1	Hazardous to the aquatic environment - chronic

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 2/9
(30605606/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:
Warning

Hazard Statement:

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H373	May cause damage to organs (Pancreas) through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P260	Do not breathe dust/gas/mist/vapours.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P361	Take off immediately all contaminated clothing.
P301 + P330	IF SWALLOWED: rinse mouth.
P391	Collect spillage.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
68479-98-1	>= 25.0 - < 50.0 %	diethylmethylbenzenediamine

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 3/9
(30605606/SDS_GEN_US/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 4/9
(30605606/SDS_GEN_US/EN)

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

7. Handling and Storage

Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves.

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 5/9
(30605606/SDS_GEN_US/EN)

Eye protection:

Safety glasses with side-shields. Wear face shield if splashing hazard exists.

Body protection:

Impermeable protective clothing

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	slight odour	
Odour threshold:		No applicable information available.
Colour:	No data available.	
pH value:		neutral to slightly alkaline
Melting point:		No applicable information available.
Boiling point:	307.78 °C	
Sublimation point:		No applicable information available.
Flash point:	135 °C	
Flammability:	not highly flammable	
Lower explosion limit:		No data available.
Upper explosion limit:		No data available.
Vapour pressure:		No applicable information available.
Density:	9.15 g/cm ³	(20 °C)
Relative density:		No applicable information available.
Bulk density:		not applicable
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:		No applicable information available.
Viscosity, kinematic:		No applicable information available.
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 6/9
(30605606/SDS_GEN_US/EN)

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Harmful if swallowed.

Oral

Type of value: ATE

Value: 1,050 mg/kg

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Causes serious eye irritation. Risk of serious damage to eyes.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity: No applicable information available.

Other Information

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 7/9
(30605606/SDS_GEN_US/EN)

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Very toxic to aquatic organisms.

Aquatic toxicity

Information on: diethylmethylbenzenediamine

Assessment of aquatic toxicity:

Very toxic (acute effect) to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Additional information

Other ecotoxicological advice:
Ecological data are not available.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 8/9
(30605606/SDS_GEN_US/EN)

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute;

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
1000 LBS	108-95-2	phenol

NFPA Hazard codes:
Health : 2 Fire: 1 Reactivity: 0 Special:

HMIS III rating
Health: 2 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2015/03/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY

Safety Data Sheet

MasterSeal M 265 PART A also CONIPUR 265Z BASE COAT PTA

Revision date : 2015/03/24
Version: 2.0

Page: 9/9
(30605606/SDS_GEN_US/EN)

UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET