according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Detonators, Electric (Class 1.4B)
- · Article number: 1076
- · Other product identifiers:

ELECTRIC SUPER™ COAL

ELECTRIC SUPER™ LP

ELECTRIC SUPER™ SP

ELECTRIC SUPER™ STARTER

ELECTRIC INSTANT

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Explosive product.

Commercial blasting applications

- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500

Salt Lake City, Utah 84121 Phone: 801-364-4800

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dnna.hse@am.dynonobel.com

· 1.4 Emergency telephone number:

CHEMTREC

1-800-424-9300 (US/Canada)

+01 703-527-3887 (International)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



exploding bomb

Expl. 1.4 H204 Fire or projection hazard.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R5: Heating may cause an explosion.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 1)

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS01

· Signal word Warning

· Hazard-determining components of labelling:

pentaerythritol tetranitrate (PETN)

diazodinitro phenol (DDNP)

Nitrocellulose, colloided, granular

lead diazide

· Hazard statements

H204 Fire or projection hazard.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P250 Do not subject to grinding/shock/friction.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment. P373 DO NOT fight fire when fire reaches explosives.

P370+P380 In case of fire: Evacuate area. P372 Explosion risk in case of fire.

P401 Store in accordance with local/regional/national/international regulations.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH201 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

- · Hazard description:
- · WHMIS-symbols:

F - Dangerously reactive material

Explosive products are not classified under WHMIS.

(Contd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 2)



- · NFPA ratings (scale 0 4) Not available.
- · HMIS-ratings (scale 0 4)

Warning: Contains lead salt(s). Long-term health hazard. Not available

· HMIS Long	Term Health Hazard Substances
13424-46-9	lead diazide
7758-97-6	lead chromate
13463-67-7	titanium dioxide
7778-74-7	potassium perchlorate

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- **Explosive Product Notice**

PREVENTION OF ACCIDENTS IN THE USE OF EXPLOSIVES - The prevention of accidents in the use of explosives is a result of careful planning and observance of the best known practices. The explosives user must remember that he is dealing with a powerful force and that various devices and methods have been developed to assist him in directing this force. He should realize that this force, if misdirected, may either kill or injure both him and his fellow workers.

WARNING - All explosives are dangerous and must be carefully handled and used following approved safety procedures either by or under the direction of competent, experienced persons in accordance with all applicable federal, state, and local laws, regulations, or ordinances. If you have any questions or doubts as to how to use any explosive product, DO NOT USE IT before consulting with your supervisor, or the manufacturer, if you do not have a supervisor. If your supervisor has any questions or doubts, he should consult the manufacturer before use.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

CAS: 78-11-5

- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

EINECS: 201-084-3

Index number: 603-035-00-5

Onst. Expl., H200

pentaerythritol tetranitrate (PETN)

(Contd. on page 4)

Printing date 22.05.2015 Revision: 22.05.2015

	(Contd. of page
CAS: 4682-03-5	diazodinitro phenol (DDNP) Xi R36/38; Xi R43; E R3 Unst. Expl., H200 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317
CAS: 9004-70-0 EC number: 603-037-0	Nitrocellulose, colloided, granular
CAS: 13424-46-9 EINECS: 236-542-1 Index number: 082-003-00-7	
	Unst. Expl., H200 Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Acute Tox. 4, H332
CAS: 7440-33-7 EINECS: 231-143-9	tungsten substance with a Community workplace exposure limit
CAS: 10294-40-3 EINECS: 233-660-5 Index number: 056-002-00-7	barium chromate Xn R20/22 Carc. 1A, H350 Acute Tox. 4, H302; Acute Tox. 4, H332
CAS: 7440-36-0 EINECS: 231-146-5	antimony substance with a Community workplace exposure limit
CAS: 7440-21-3 EINECS: 231-130-8	silicon F R11 Flam. Sol. 2, H228
CAS: 1314-41-6 EINECS: 215-235-6 Index number: 082-001-00-6	orange lead ☐ T Repr. Cat. 1, 3 R61; ☐ Xn R62-20/22; ☐ N R50/53 R33 ☐ Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 ☐ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ☐ Acute Tox. 4, H302; Acute Tox. 4, H332
CAS: 7439-92-1 EINECS: 231-100-4	lead ▼ T Repr. Cat. 1 R60-61-48/23/25; N R50/53 Repr. 1A, H360FD; STOT RE 1, H372 Aquatic Acute 1, H400; Aquatic Chronic 1, H410
CAS: 7758-97-6 EINECS: 231-846-0 Index number: 082-004-00-2	lead chromate ☐ T Carc. Cat. 2, Repr. Cat. 1, 3 R45-61; Xn R62; N R50/53 R33 ☐ Carc. 1B, H350; Repr. 1A, H360Df; STOT RE 2, H373 ☐ Aquatic Acute 1, H400; Aquatic Chronic 1, H410

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

		(Contd. of page 4)
CAS: 7782-49-2	selenium	
EINECS: 231-957-4	№ T R23/25	
Index number: 034-001-00-2	R33-53	
	Acute Tox. 3, H301; Acute Tox. 3, H331	
	♦ STOT RE 2, H373	
	Aquatic Chronic 4, H413	
CAS: 13463-67-7	titanium dioxide	
EINECS: 236-675-5	substance with a Community workplace exposure limit	
CAS: 7727-43-7	barium sulphate, natural	
EINECS: 231-784-4	substance with a Community workplace exposure limit	
CAS: 7440-42-8	boron	
EINECS: 231-151-2		
CAS: 7778-74-7	potassium perchlorate	
EINECS: 231-912-9	X Xn R22; A O R9	
Index number: 017-008-00-5	♠ Ox. Sol. 1, H271	
· SVHC		
13424-46-9 lead diazide		
7758-97-6 lead chromate	7758-97-6 lead chromate	
1314-41-6 orange lead		
A dditional information.		

· Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret. For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Unlikely route of exposure.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Generally the product does not irritate the skin.

Wash with soap and water.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed Blast injury if mishandled.
- · Hazards Danger of blast or crush-type injuries.

(Contd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 5)

· 4.3 Indication of any immediate medical attention and special treatment needed

Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: DO NOT fight fire when fire reaches explosives.
- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

DO NOT ATTEMPT TO FIGHT FIRES INVOLVING EXPLOSIVE MATERIALS. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions. Can explode or detonate under fire conditions. Burning material may produce toxic vapors. It is recommended that users of explosives material be familiar with the Institute of Makers of Explosives Safety Library publications.

Product may explode if burned in confined space. Individual cartridges may explode. Mass explosion of many cartridges at once is unlikely.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Eliminate all ignition sources if safe to do so.

Flammability Classification: (defined by 29 CFR 1910.1200) Explosive. Can explode under fire conditions. Individual devices will randomly explode. Will not mass explode if multiple devices are involved. Burning material may produce toxic and irritating vapors. In unusual cases, shrapnel may be thrown from exploding devices under containment. See 2008 Emergency response Guidebook for further information.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Protect from heat.

Evacuate area.

Isolate area and prevent access.

- 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose unusable material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 7)



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 6)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Handle with care. Avoid jolting, friction and impact.

Use only in well ventilated areas.

Do not subject to grinding/shock/friction.

· Information about fire - and explosion protection:

Protect from heat.

Emergency cooling must be available in case of nearby fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep away from heat.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

011 00111101 p	541411101010
· Ingredients v	with limit values that require monitoring at the workplace:
13424-46-9 le	ead diazide
PEL (USA)	Long-term value: 0,05 mg/m³ as Pb; See 29 CFR 1910,1025
REL (USA)	Long-term value: 0,05* mg/m³ as Pb;*8-hr TWA; See Pocket Guide App. C
TLV (USA)	Long-term value: 0,05 mg/m³ as Pb; BEI
EL (Canada)	Long-term value: 0,05 mg/m³ as Pb; IARC 2A, R
10294-40-3 b	parium chromate
PEL (USA)	Long-term value: 0,005* mg/m³ Ceiling limit: 0,1** mg/m³ *as Cr(VI) **as CrO3; see 29 CFR 1910,1026
REL (USA)	Long-term value: 0,0002 mg/m³ as Cr; See Pocket Guide Apps. A and C
TLV (USA)	Long-term value: 0,01 mg/m³ as Cr
	(Contd. on page 8

Printing date 22.05.2015 Revision: 22.05.2015

		(Contd. of page
EL (Canada)	Long-term value: 0,01 mg/m³ as Cr; ACGIH A1 IARC 1	
7440-36-0 an	timony	
PEL (USA)	Long-term value: 0,5 mg/m³ as Sb	
REL (USA)	Long-term value: 0,5 mg/m³ as Sb	
TLV (USA)	Long-term value: 0,5 mg/m³ as Sb	
EL (Canada)	Long-term value: 0,5 mg/m ³	
EV (Canada)	Long-term value: 0,5 mg/m³	
7758-97-6 lea		
IOELV (EU)	Long-term value: 2 mg/m³ as Cr	
PEL (USA)	Long-term value: 0,005* mg/m³ Ceiling limit: 0,1** mg/m³ *as Cr(VI) **as CrO3; see 29 CFR 1910,1026	
REL (USA)	Long-term value: 0,0002 mg/m³ as Cr; See Pocket Guide Apps. A and C	
TLV (USA)	Long-term value: 0,05* 0,012** mg/m³ *as Pb; BEI; **as Cr	
EL (Canada)	Long-term value: 0,05* 0,012** mg/m³ ACIGH A2, IARC 2A; R; *as Pb;**as Cr	
EV (Canada)	Long-term value: 0,012* 0,05** mg/m³ *as Cr, **as Pb	
7440-33-7 tui	ngsten	
PEL (USA)	and insoluble compounds, as We	
REL (USA)	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³ as W	
TLV (USA)	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³ as W	
EL (Canada)	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³ as W	
EV (Canada)	Short-term value: 10* 3** mg/m³ Long-term value: 5* 1** mg/m³ (as tungsten; compds.:*water-insol.;**water-sol.	
7440-21-3 sil	con	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	

Printing date 22.05.2015 Revision: 22.05.2015

REL (USA)	Long-term value: 10* 5** mg/m³	(Contd. of page 8)
KEL (USA)	*total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
1 1	Long-term value: 10* 3** mg/m³	
	*total dust;**respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
1314-41-6 or	range lead	
PEL (USA)	Long-term value: 0,05 mg/m³ as Pb; See 29 CFR 1910,1025	
REL (USA)	Long-term value: 0,05* mg/m³ as Pb;*8-hr TWA; See Pocket Guide App. C	
TLV (USA)	Long-term value: 0,05 mg/m³ as Pb; BEI	
EL (Canada)	Long-term value: 0,05 mg/m³ as Pb; IARC 2A, R	
EV (Canada)	Long-term value: 0,05 mg/m³ as Pb, Skin (organic compounds)	
7782-49-2 se	elenium	
PEL (USA)	Long-term value: 0,2 mg/m³ as Se	
REL (USA)	Long-term value: 0,2 mg/m³ as Se	
TLV (USA)	Long-term value: 0,2 mg/m³ as Se	
EL (Canada)	Long-term value: 0,1 mg/m³	
EV (Canada)	Long-term value: 0,2 mg/m³	
13463-67-7 t	itanium dioxide	
PEL (USA)	Long-term value: 15* mg/m³ *total dust	
REL (USA)	See Pocket Guide App. A	
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
7727-43-7 ba	arium sulphate, natural	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
		Contd. on page 10)

Printing date 22.05.2015 Revision: 22.05.2015

		(Contd. of page 9)
REL (USA)		(Common page of
	*total dust **respirable fraction	
TLV (USA)	Long-term value: 5* mg/m³ *inhalable fraction; E	
EL (Canad	a) Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction	
EV (Canad	a) Long-term value: 10 mg/m³ total dust	
	further relevant information available. further relevant information available.	
· Ingredient	s with biological limit values:	
13424-46-9	lead diazide	
BEI (USA)	30 µg/100 ml Medium: blood Time: not critical Parameter: Lead	
10294-40-3	barium chromate	
BEI (USA)	25 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Total chromium (fume)	
	10 μg/L Medium: urine Time: increase during shift Parameter: Total chromium (fume)	
7758-97-6	lead chromate	
BEI (USA)	30 µg/100 ml Medium: blood Time: not critical Parameter: Lead	
	10 μg/100 ml Medium: blood Time: not critical Parameter: Lead (women of child bearing potential)	
	orange lead	
	30 µg/100 ml Medium: blood Time: not critical Parameter: Lead	
· Additional	information: The lists valid during the making were used as basis.	(Contd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 10)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not required under normal conditions of use.

Respiratory protection may be required after product use.

· Protection of hands:

Wear gloves for the protection against mechanical hazards according to NIOSH or EN 388.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

Face protection

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

Organizational measures should be in place for all activities involving this product.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Solid material

Colour: According to product specification

Odour:
 Odour threshold:
 pH-value:
 Odourless
 Not determined.
 Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.

Flash point:

Not applicable.

(Contd. on page 12)



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 11)

• Flammability (solid, gaseous): Fire or projection hazard.

Auto/Self-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

Self-igniting: Product is not self-igniting.

• **Danger of explosion:** Heating may cause an explosion.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure:
Not applicable.

Density:
Relative density
Vapour density
Vapour density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

· Solubility in / Miscibility with

water: Variable, dependent upon product composition and packaging.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

9.2 Other information
 No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

· 10.3 Possibility of hazardous reactions

Danger of explosion.

Toxic fumes may be released if heated above the decomposition point.

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Leadoxide vapour

Nitrogen oxides

Chlorine compounds

Danger of forming toxic pyrolysis products.

(Contd. on page 13)



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

Toxic metal oxide smoke

(Contd. of page 12)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

7758-97-6 lead chromate

Oral LD50 12000 mg/kg (mouse)

7782-49-2 selenium

Oral LD50 6700 mg/kg (rat)

- Primary irritant effect:
- · on the skin:

Not a skin irritant in unused form. Vapors/particles from used product are possibly irritating to skin.

· on the eye:

Not an eye irritant in unused form. Vapors/particles from used product are possibly irritating to eyes.

- · Sensitisation: No sensitising effects known.
- · Subacute to chronic toxicity: No further relevant information available.
- · Acute effects (acute toxicity, irritation and corrosivity): Danger of blast or crush-type injuries.
- · Repeated dose toxicity: No further relevant information available.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential May be accumulated in organism
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

Very toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 14)



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 13)

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Damaged materials pose a danger to anyone in the immediate area; consult experts for disposal of damaged products.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, IMDG, IATA UN0255

· 14.2 UN proper shipping name

DETONATORS, ELECTRIC
ADR

DETONATORS, ELECTRIC
0255 DETONATORS, ELECTRIC

· 14.3 Transport hazard class(es)

· DOT



• Class 1.4 • Label 1.4

· ADR, IMDG, IATA



• Class 1.4 • Label 1.4B

· 14.4 Packing group · DOT, ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

(Contd. on page 15)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and **OSHA GHS**

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 14)

· Special marking (IATA):

Prohibited from Transport in Passenger Aircraft.



Cargo Aircraft Only.

· 14.6 Special precautions for user Not applicable. · EMS Number: F-B,S-X

· Segregation groups Lead and its compounds

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 0

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Tunnel restriction code

· IMDG

· Limited quantities (LQ) 0

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

UN0255, DETONATORS, ELECTRIC, 1.4B, II · UN "Model Regulation":

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA

· Section 355	(extremely	hazardous	subs	tances):
---------------	------------	-----------	------	----------

None of the ingredients are listed.

· Section	313	(Specific	toxic	chemical	listings).

	lead diazide
10294-40-3	barium chromate

7440-36-0 antimony

7758-97-6 lead chromate

1314-41-6 orange lead

7782-49-2 selenium

7727-43-7 barium sulphate, natural

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65 (California):

· Chemicals known to cause cancer:

13424-46-9 lead diazide

(Contd. on page 16)

Printing date 22.05.2015 Revision: 22.05.2015

10294-40-3	barium chromate	(Contd. of page
	lead chromate	
	orange lead	
	titanium dioxide	
		au famalaa.
	known to cause reproductive toxicity for barium chromate	or temales:
	lead chromate	
	known to cause reproductive toxicity for	or males:
	barium chromate	
7758-97-6	lead chromate	
· Chemicals	known to cause developmental toxicity	:
13424-46-9	lead diazide	
10294-40-3	barium chromate	
7758-97-6	lead chromate	
· Carcinoger	nic Categories	
•	onmental Protection Agency)	
13424-46-9	lead diazide	B2
10294-40-3	barium chromate	A(inh), D(oral), K/L(inh), CBD(ora
	lead chromate	К
1314-41-6	orange lead	B2
7782-49-2	selenium	D
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
7440-42-8	boron	I (oral)
7778-74-7	potassium perchlorate	NL
· IARC (Inter	national Agency for Research on Cance	er)
13424-46-9	lead diazide	[2
10294-40-3	barium chromate	1
7758-97-6	lead chromate	1
1314-41-6	orange lead	2
7782-49-2	selenium	3
13463-67-7	titanium dioxide	2
· TLV (Thres	hold Limit Value established by ACGIH)	
13424-46-9	lead diazide	ļ.
10294-40-3	barium chromate	ļ.
7758-97-6	lead chromate	F
1314-41-6	orange lead	F
-		

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

	(Contd. of page 16)		
· NIOSH-Ca (· NIOSH-Ca (National Institute for Occupational Safety and Health)		
10294-40-3	barium chromate		
	lead chromate		
13463-67-7	titanium dioxide		

· Canada

· Canadian Domestic Substances List (DSL)

Some components are listed on the NDSL.

All ingredients are listed.		
· Canadian Ingredient Disclosure list (limit 0.1%)		
10294-40-3	barium chromate	
7758-97-6	lead chromate	
7782-49-2	selenium	
· Canadian Ingredient Disclosure list (limit 1%)		
7440-36-0	·	
7440-33-7	tungsten	

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Substances of very high concern (SVHC) according to REACH, Article 57		
	13424-46-9	lead diazide
ĺ	7758-97-6	lead chromate
ĺ	1314-41-6	orange lead

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

· Relevant phrases

H200 Unstable explosives.

H201 Explosive; mass explosion hazard.

H228 Flammable solid.

(Contd. on page 18)



Revision: 22.05.2015 Printing date 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

L1074	May source fire or explosion, etrong evidinor		
H271	May cause fire or explosion; strong oxidiser.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H332	Harmful if inhaled.		
H350	May cause cancer.		
H360Df	May damage the unborn child. Suspected of damaging fertility.		
H360FD	May damage fertility. May damage the unborn child.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
	e e elle e e e e elle e e elle e e e e		
R11	Highly flammable.		
R20/22	Harmful by inhalation and if swallowed.		
R22	Harmful if swallowed.		
R23/25	Toxic by inhalation and if swallowed.		
R3	Extreme risk of explosion by shock, friction, fire or other sources of ignition.		
R33	Danger of cumulative effects.		
R36/38	Irritating to eyes and skin.		
R43	May cause sensitisation by skin contact.		
R45	May cause cancer.		
R48/23/2	5 Toxic: danger of serious damage to health by prolonged exposure through inhalation and if		
	swallowed.		
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic		
	environment.		
R53	May cause long-term adverse effects in the aquatic environment.		
R60	May impair fertility.		
R61	May cause harm to the unborn child.		
R62	Possible risk of impaired fertility.		
R9	Explosive when mixed with combustible material.		
	·		
· Apprevia	ations and acronyms: ord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the		
Internationa	Il Carriage of Dangerous Goods by Road)		
	national Maritime Code for Dangerous Goods		
	epartment of Transportation		
	national Air Transport Association		
	ally Harmonised System of Classification and Labelling of Chemicals erican Conference of Governmental Industrial Hygienists		
	uropean Inventory of Existing Commercial Chemical Substances		
ELINCS: Et	ELINCS: European List of Notified Chemical Substances		
	CAS: Chemical Abstracts Service (division of the American Chemical Society)		
NFPA: National Fire Protection Association (USA)			
HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH)			
			PNEC: Pred
LC50: Letha	al concentration, 50 percent		
	II and an name ture		

(Contd. on page 19)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and **OSHA GHS**

Printing date 22.05.2015 Revision: 22.05.2015

Trade name: Detonators, Electric (Class 1.4B)

(Contd. of page 18)

LD50: Lethal dose, 50 percent

Expl. 1.1: Explosives, Division 1.1

Expl. 1.4: Explosives, Division 1.4

Unst. Expl.: Explosives, Unstable explosives
Flam. Sol. 2: Flammable solids, Hazard Category 2

Ox. Sol. 1: Oxidising Solids, Hazard Category 1

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1A: Carcinogenicity, Hazard Category 1A Carc. 1B: Carcinogenicity, Hazard Category 1B

Repr. 1A: Reproductive toxicity, Hazard Category 1A Repr. 1A: Reproductive toxicity, Hazard Category 1A

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com