

SAFETY DATA SHEET.

Issuing date 07-Jan-2015

Number

Revision Date 07-Jan-2015

Version 2.07

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

<u>Product identifier</u> Product name	80-699 FOUR WAY LUBE WITH PTFE
Recommended use of the chemical and restrictions on use	<u>L</u>
Product code	F00518
<u>Product Type</u> Synonyms	Extremely flammable aerosol None
Supplier's details	
Recommended Use Uses advised against	Penetrating lubricant with PTFE.
Manufactured For: Kimball Midwest 4800 Roberts Rd. Columbus, OH 43228	
Emergency telephone number Chemical Emergency Phone Number	Chemtrec 1-800-424-9300
Company Emergency Phone	800-233-1294

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

Emergency Overview

<u>GHS Label elements, including</u> precautionary statements

DANGER

Hazard Statements

Causes skin irritation May cause drowsiness or dizziness May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated



Appearance Slightly Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash hands thoroughly after handling Wear protective gloves Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Protect from sunlight. Store in a well-ventilated place Keep container tightly closed. Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

· Toxic to aquatic life with long lasting effects

0.00000938 %% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	35-45
NAPHTHENIC OIL, SEVERELY HYDROT	64742-52-5	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
KEROSENE	8008-20-6	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, and clothing.Avoid breathing, vapors, mist, or gas.	
Eye contact	Rinse immediately with plenty of water and seek medical advice.	
Skin contact	Wash off immediately with plenty of water. Remove and wash contaminated clothing before re-use. Get medical attention immediately if symptoms occur.	
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.	
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.	
Most important symptoms/effects,	acute and delayed	
Main Symptoms	May cause skin irritation. Inhalation causing Central Nervous System effects. ingestion causing lung damage.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable Extinguishing Media

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

<u>Protective Equipment and Precautions for Firefighters</u> As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective ed	quipment and emergency procedures	
Personal precautions	Use with adequate ventiliation to keep the exposure levels below the OELS.	
Environmental precautions		
Environmental precautions	Report spills as required by local and federal regulations.	
Methods and materials for contain	nent and cleaning up	
Methods for Containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Contain liquid and collect with an inter, non-combustible material.	
7. HANDLING AND STORAGE		
Precautions for safe handling		
Advice on safe handling	Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventiliation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.	
Conditions for safe storage, including any incompatibilities		
Technical measures/Storage conditions	Keep containers tightly closed in a dry, cool and well-ventilated place.	
Incompatible products	Store away from strong oxidizers and acids.	
Aerosol Level	3	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³

F00518 - 80-699 FOUR WAY LUBE WITH PTFE

Revision Date 07-Jan-2015

KEROSENE	TWA: 200 mg/m ³ total	-	TWA: 100 mg/m ³
8008-20-6	hydrocarbon vapor application		
	restricted to conditions in which		
	there are negligible aerosol		
	exposures		
	Skin - potential significant		
	contribution to overall exposure		
	by the cutaneous route		
ACCIH: (Amorican Conference of)	Covernmental Industrial Uvaienists		^

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
Exposure controls	
Engineering Measures	Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.
Individual protection measures, su	ch as personal protective equipment
Eye/Face Protection	Safety glasses with side-shields.
Skin and body protection	Chemical resistant apron. Protective gloves.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Appearance	Aerosol Slightly Hazy	Odor	Solvent
Color	amber	Odor Threshold	No information available
_			
Property	<u>Values</u>	Remarks • Methods	
pH Malvin a franciscus a sint	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available	Deced on prepallant	
Flash Point	-96.4 °C / -141 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit	No information available		
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	0.805		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/wat			
Autoignition temperature	No information available	Not applicable	
Decomposition temperature	No information available		
Viscosity	No information available		
Explosive properties	No information available		
Other information			

24.12

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong oxidizers and acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known information
Inhalation	Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.
Eye contact	May cause slight irritation.
Skin contact	Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting . Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Contact with eyes may cause irritation. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Carcinogenicity	There are no known carcinogenic chemicals in this product.
Reproductive toxicity	The ingredients are not reproductive hazards.

Specific target organ systemic	May cause drowsiness and dizziness.			
toxicity (single exposure)				
Specific target organ systemic	No information available.			
toxicity (repeated exposure)				
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.			
Target Organ Effects	Central nervous system, Eyes, Respiratory system, Skin.			
Aspiration hazard	May be fatal if swallowed and enters airways.			
Numerical measures of toxicity - Product Information				

 Unknown Acute Toxicity
 0.00000938 %% of the mixture consists of ingredient(s) of unknown toxicity

 The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 10656 mg/kg

 ATEmix (dermal)
 4262 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
NAPHTHENIC OIL, SEVERELY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment	
Waste Disposal Methods	Dispose of in accordance with federal, state, and local regulations.
Contaminated packaging	Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground

CONSUMER COMMODITY ORM-D or LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	Х	X	Х	х	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERELY HYDROT	Х	X	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	X	Х	Not listed	Х	Х	Х	Х
KEROSENE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

No warning required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE	Х	Х	Х
8008-20-6			

EPA Pesticide Registration Number Not applicable

<u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards	
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B	
Prepared By	Regulato	ory Affairs			
Issuing date	07-Jan-2	2015			
Revision Date	07-Jan-2	2015			
Revision Note					
(M)SDS sections updat	ted				
Disclaimer					
TI				I STORE AND STREET	

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet