


**SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** KILZ® Original  
**Product Code:** 1000  
**SDS Manufacturer Number:** 1000  
**Manufacturer Name:** Masterchem Industries LLC  
**Address:** 3135 Old Highway M  
 Imperial, MO 63052-2834  
**General Phone Number:** (636) 942-2510  
**General Fax Number:** (636) 942-3663  
**Customer Service Phone Number:** (800) 325-3552  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**Canutec:** In Canada, call CANUTEC: (613) 996-6666 (call collect)



<b>HMIS</b>	
<b>Health Hazard</b>	<b>1</b>
<b>Fire Hazard</b>	<b>3</b>
<b>Reactivity</b>	<b>1</b>
<b>Personal Protection</b>	

**SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS#</b>	<b>Ingredient Percent</b>
Silicate, mica	12001-26-2	10 - 30 by weight
Calcium carbonate (limestone)	1317-65-3	5 - 10 by weight
Rutile	1317-80-2	5 - 10 by weight
Aliphatic Hydrocarbon	64742-49-0	10 - 30 by weight
Amorphous Silica	112926-00-8	1 - 5 by weight
Nepheline Syenite	37244-96-5	1 - 5 by weight
Titanium dioxide	13463-67-7	5 - 10 by weight
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	10 - 30 by weight

**SECTION 3 : HAZARDS IDENTIFICATION**

**Emergency Overview:** Flammable. Irritant.  
**Potential Health Effects:**  
**Eye:** May cause irritation.  
**Skin:** May cause irritation.  
**Inhalation:** Prolonged or excessive inhalation may cause respiratory tract irritation.  
**Ingestion:** Harmful if swallowed. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation.  
**Chronic Health Effects:** Prolonged or repeated contact can result in defatting and drying of the skin, which may result in skin irritation and dermatitis (rash). Repeated or prolonged inhalation may cause toxic effects.  
**Signs/Symptoms:** Overexposure can cause headaches, dizziness, nausea, and vomiting.  
**Target Organs:** Eyes. Skin. Respiratory system. Digestive system. Central nervous system. Kidney.  
**Aggravation of Pre-Existing Conditions:** May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

**SECTION 4 : FIRST AID MEASURES**

**Eye Contact:** Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.  
**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.  
**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Note to Physicians:** Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

## SECTION 5 : FIRE FIGHTING MEASURES

<b>Flammable Properties:</b>	Flammable liquid.
<b>Flash Point:</b>	75°F (23.9°C)
<b>Flash Point Method:</b>	SETA
<b>Lower Flammable/Explosive Limit:</b>	0.8
<b>Upper Flammable/Explosive Limit:</b>	8.9
<b>Fire Fighting Instructions:</b>	Flammable. Cool fire-exposed containers using water spray.
<b>Extinguishing Media:</b>	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Unusual Fire Hazards:</b>	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.
<b>NFPA Ratings:</b>	
NFPA Health:	1
NFPA Flammability:	3
NFPA Reactivity:	1

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

<b>Personnel Precautions:</b>	Use proper personal protective equipment as listed in section 8.
<b>Environmental Precautions:</b>	Avoid runoff into storm sewers, ditches, and waterways.
<b>Spill Cleanup Measures:</b>	Remove all sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal.

## SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.
<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
<b>Work Practices:</b>	To reduce potential for static discharge, bond and ground containers when transferring material.
<b>Special Handling Procedures:</b>	Do not reuse containers without proper cleaning or reconditioning.
<b>Hygiene Practices:</b>	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### **Silicate, mica :**

Guideline ACGIH:	TLV-TWA: 3 mg/m3 (Respirable)
Guideline OSHA:	OSHA-TWA: 20 mg/m3

**Amorphous Silica :**

Guideline ACGIH: TLV-TWA: 10 mg/m<sup>3</sup>  
Guideline OSHA: OSHA-TWA: 20 mg/m<sup>3</sup>

**Titanium dioxide :**

Guideline ACGIH: TLV-TWA: 10 mg/m<sup>3</sup>  
Guideline OSHA: OSHA-TWA: 15 mg/m<sup>3</sup>

**Distillates (petroleum), hydrotreated light; Kerosine - unspecified :**

Guideline ACGIH: TLV-TWA: 200 mg/m<sup>3</sup> (Negligible aerosol exposures)

**SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES**

Physical State Appearance: Liquid.  
Boiling Point: No Data  
Melting Point: No Data  
Density: 10 - 12 Lbs./gal.  
Vapor Density: Greater than 1 (Air = 1).  
pH: No Data  
Molecular Formula: Mixture  
Molecular Weight: Mixture  
Flash Point: 75°F (23.9°C)  
Flash Point Method: SETA  
VOC Content: Material VOC: 442 gm/l (Includes Water)  
Coating VOC.: 442 gm/l (Excludes Water)

**SECTION 10 : STABILITY and REACTIVITY**

Chemical Stability: Stable under normal temperatures and pressures.  
Hazardous Polymerization: Not reported.  
Conditions to Avoid: Heat, flames, ignition sources, and sparks. Incompatible materials. Freezing or temperatures below 0°C (32°F).  
Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

**SECTION 11 : TOXICOLOGICAL INFORMATION****Silicate, mica :**

RTECS Number: VV8760000

**Calcium carbonate (limestone) :**

RTECS Number: EV9580000

**Rutile :**

RTECS Number: VM2940000

**Amorphous Silica :**

RTECS Number: VV7315000

**Nepheline Syenite :**

RTECS Number: QP9365000

**Titanium dioxide :**

RTECS Number: XR2275000

Skin: Administration onto the skin - Human Standard Draize test.: 300 ug/3D (Intermittent) (RTECS)

Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans.

**Distillates (petroleum), hydrotreated light; Kerosine - unspecified :**

RTECS Number: OA5504000

**SECTION 12 : ECOLOGICAL INFORMATION**

Ecotoxicity: No ecotoxicity data was found for the product.  
Environmental Fate: No environmental information found for this product.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines,

if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

**Important Disposal Information:** DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

## SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Paint.  
DOT UN Number: UN1263  
DOT Hazard Class: 3  
DOT Packing Group: III  
DOT Exemption: Consumer Commodity, ORM-D for container less than 1.3 gallons or 5 liters

## SECTION 15 : REGULATORY INFORMATION

### Silicate, mica :

TSCA Inventory Status: Not listed  
State Regulations: Listed in the New Jersey State Right to Know List.  
Listed in the Pennsylvania State Hazardous Substances List.  
Canada DSL: Listed

### Calcium carbonate (limestone) :

TSCA Inventory Status: Listed  
State Regulations: Listed in the Pennsylvania State Hazardous Substances List.

### Rutile :

TSCA Inventory Status: Listed  
State Regulations: Listed in the Pennsylvania State Hazardous Substances List.  
Canada DSL: Listed

### Aliphatic Hydrocarbon :

TSCA Inventory Status: Listed  
Canada DSL: Listed

### Amorphous Silica :

TSCA Inventory Status: Not listed  
Canada DSL: Listed

### Nepheline Syenite :

TSCA Inventory Status: Not listed  
Canada DSL: Listed

### Titanium dioxide :

TSCA Inventory Status: Listed  
State Regulations: Listed in the New Jersey State Right to Know List.  
Listed in the Pennsylvania State Hazardous Substances List.  
Canada DSL: Listed

### Distillates (petroleum), hydrotreated light; Kerosine - unspecified :

TSCA Inventory Status: Listed  
Canada DSL: Listed

## SECTION 16 : ADDITIONAL INFORMATION

### HMIS Ratings:

HMIS Health Hazard: 1  
HMIS Fire Hazard: 3  
HMIS Reactivity: 1

SDS Creation Date: June 26, 2006  
SDS Revision Date: October 15, 2013  
MSDS Revision Notes: Quarterly formula update  
SDS Format:  
MSDS Author: Actio Corporation

**Disclaimer:** This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use.

We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

**Trademark:**

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.