

Revision date: 2014/06/30 Page: 1/11
Version: 2.1 (30605598/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterKure CC 160WB also KURE N SEAL WB

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

Details of the supplier of the safety data sheet

Company: BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No data available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq. 3 Flammable liquid Resp. Sens. 1 Respiratory sensitization Skin Sens. 1 Skin sensitization Carc. Carcinogenicity Repr. 2 (fertility) Reproductive toxicity Repr. 1B (unborn child) Reproductive toxicity

Aquatic Acute 3 Hazardous to the aquatic environment - acute Aquatic Chronic 3 Hazardous to the aquatic environment - chronic

^{*} The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2014/06/30 Page: 2/11 Version: 2.1 (30605598/SDS GEN US/EN)

Label elements

Pictogram:



Signal Word: Danger

Hazard Statement:

H226 Flammable liquid and vapour.

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H360 May damage the unborn child. Suspected of damaging fertility.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P273 Avoid release to the environment.

P243 Take precautionary measures against static discharge.

P202 Do not handle until all safety precautions have been read and

understood.

P284 [In case of inadequate ventilation] wear respiratory protection.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P233 Keep container tightly closed. P242 Use only non-sparking tools.

P240 Ground/bond container and receiving equipment.

Precautionary Statements (Response):

P304 + P341 + P311 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest

in a position comfortable for breathing. Call a POISON CENTER or

doctor/physician.

P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P303 + P352 IF ON SKIN (on hair): Wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or

doctor/physician.

P362 + P364 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use (...) for extinction.

Precautionary Statements (Storage): P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

Revision date: 2014/06/30 Page: 3/11 Version: 2.1 (30605598/SDS GEN US/EN)

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

WARNING:

COMBUSTIBLE LIQUID AND VAPOR.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM

DAMAGE.

Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.

CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

May damage fertility or the unborn child.

Keep container tightly closed.

Avoid all sources of ignition: heat, sparks, open flame.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
64742-95-6	>= 3.0 - < 5.0 %	solvent naphtha
95-63-6	>= 1.0 - < 3.0 %	1,2,4-trimethylbenzene
25340-17-4	>= 0.2 - < 0.3 %	Benzene, diethyl-
84-74-2	>= 0.2 - < 0.3 %	dibutyl phthalate
7727-54-0	>= 0.0 - < 0.2 %	Peroxydisulfuric acid ([(HO)S(O)2]2O2), diammonium salt

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
64742-95-6	>= 1.0 - < 5.0 %	solvent naphtha
95-63-6	>= 1.0 - < 5.0 %	1,2,4-trimethylbenzene
107-21-1	>= 0.1 - < 1.0 %	ethylene glycol
67-56-1	>= 0.1 - < 1.0 %	Methanol
84-74-2	>= 0.1 - < 1.0 %	dibutyl phthalate
112-34-5	>= 0.1 - < 1.0 %	Butyl diglycol

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

Revision date: 2014/06/30 Page: 4/11 Version: 2.1 (30605598/SDS GEN US/EN)

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eves:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see

section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Revision date: 2014/06/30 Page: 5/11 Version: 2.1 (30605598/SDS GEN US/EN)

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: High density polyethylene (HDPE)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 5 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 40 °F

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

dibutyl phthalate OSHA PEL PEL 5 mg/m3;

ACGIH TLV TWA value 5 mg/m3;

1,2,4-trimethylbenzene

ACGIH TLV TWA value 25 ppm;

Peroxydisulfuric acid

([(HO)S(O)2]2O2), ACGIH TLV TWA value 0.1 mg/m3 (persulfate);

diammonium salt

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Revision date: 2014/06/30 Page: 6/11 Version: 2.1 (30605598/SDS GEN US/EN)

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form: liquid

Odour: characteristic, slight odour

Odour threshold: No applicable information available.

Colour: milky white

pH value: slightly alkaline

Melting point: No applicable information available.

Boiling point: 153.33 - 205.00

°C

Sublimation No applicable information available.

temperature:

Flash point: 43.33 °C
Flammability: Flammable.
Lower explosion limit: 0.9 %(V)
Upper explosion limit: 15.3 %(V)

Vapour pressure: The product has not been tested.

Density: 1 g/cm3 (20 °C)

Relative density: No applicable information available.

Bulk density:

Vapour density:

Partitioning coefficient noottanol/water (log Pow):

not applicable

Heavier than air.

No data available.

Viscosity, dynamic:

Viscosity, kinematic:

No applicable information available.

No applicable information available.

The product has not been tested.

Solubility (quantitative):

No applicable information available.

Solubility (qualitative): No applicable information available.

Evaporation rate: No applicable information available. Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

Revision date: 2014/06/30 Page: 7/11 Version: 2.1 (30605598/SDS GEN US/EN)

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: No applicable information available.

Ora

No applicable information available.

<u>Inhalation</u>

No applicable information available.

Derma

No applicable information available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: No applicable information available.

Sensitization

Assessment of sensitization: The product has not been tested. The statement has been derived from the properties of the individual components.

Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No applicable information available.

Genetic toxicity

Revision date: 2014/06/30 Page: 8/11 Version: 2.1 (30605598/SDS GEN US/EN)

Assessment of mutagenicity: No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: cumene

Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals.

Information on: ethylene glycol

Assessment of teratogenicity: In animal studies the substance caused malformations when given at high doses.

However, the relevance of this result for humans is unclear.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely harmful for aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

The product has not been tested.

Additional information

Other ecotoxicological advice:

May cause long-term adverse effects in the aquatic environment.

Revision date: 2014/06/30 Page: 9/11 Version: 2.1 (30605598/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class: C Packing group: III

ID number: NA 1993 Hazard label: CBL

Proper shipping name: COMBUSTIBLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA)

Classified as combustible liquid in containers greater than 119

gallons.

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1993

Hazard label: 3 Marine pollutant: NO

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA)

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III

ID number: UN 1993

Hazard label: 3

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire

EPCRA 313:

Revision date: 2014/06/30 Page: 10/11 Version: 2.1 (30605598/SDS GEN US/EN)

CAS NumberChemical name95-63-61,2,4-trimethylbenzene

CERCLA RQ CAS Number Chemical name

5000 LBS 67-56-1; 98-82-8; Methanol; cumene; ethylene glycol

107-21-1

1000 LBS 100-41-4 ethylbenzene 100 LBS 1330-20-7; 123- Xylene; 1,4-dioxane

91-1

10 LBS 75-21-8; 84-74-2 Ethylene Oxide; dibutyl phthalate

State regulations

State RTK	CAS Number	Chemical name
MA, NJ, PA	95-63-6	1,2,4-trimethylbenzene
MA, NJ, PA	107-21-1	ethylene glycol
MA, NJ, PA	67-56-1	Methanol
MA, NJ, PA	84-74-2	dibutyl phthalate
NJ, PA	112-34-5	Butyl diglycol

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 0 Special:

HMIS III rating

Health: 2^m Flammability: 2 Physical hazard:0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2014/06/30

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE

Revision date : 2014/06/30 Page: 11/11 Version: 2.1 (30605598/SDS_GEN_US/EN)

SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET