Continental Cement Company, L.L.C. 10107 Hwy 79 South Hannibal, MO 63401 Phone: 573.221.1740 Fax: 573.221.8487



Safety Data Sheet For <u>Portland Cement(Type I/II,III)</u>

Section 1 – Product and Company Information 1.1 Product Identifier Identify: Portland Cement(Type I/II, III) Synonyms: Portland Cement 1.2 Identified Use Use: Acts as a binding agent in concrete and mortar work. Manufacturer Name: Continental Cement Address: 10107 Highway 79 Day T Hannibal, Mo. 63401

Telephone # for Information: 573.221.1740 Last Updated: 4/27/15 *Transportation Emergency Telephone #'s:* Day Time: 573.221.1740 Night Time: 573.221.1740

Website:www.continentalcement.com

Section 2 – Hazardous Identification

2.1- Classification of the Substance or Material

GHS-US Classification-(Category) Acute Toxicity Oral: 4 Acute Toxicity Dermal: 4 Skin Corrosion/Irritation: 1B Eye Damage: 1 Respiratory Sensitization: 1 Skin Sensitization: Category 1 Carcinogenicity: 1A Specific Target Organ Toxicity: 3



Hazard Statements:

- H 302: Harmful if Swallowed
- H312: Harmful in Contact With Skin
- H314: Causes Severe Skin Burns and Eye Damage
- H318: Causes Serious Eye Damage
- H335: May Cause Allergy or Asthma Symptoms or Breathing Difficulties if Inhaled
- H317: May cause an Allergic Reaction
- H350: May Cause Cancer

Precautionary Statements

Prevention Statements

- P264: Wash thoroughly after handling
- P270: Do not eat, drink, or smoke when using this product
- P280: Wear protective gloves, protective clothing, eye protection, face protection
- P361: Remove contaminated clothing and wash before reuse
- P201: Obtain special instructions before use

P260: Do not breathe dusts

- P271: Use outdoors or in a well-ventilated area
- P284: In case of inadequate ventilation: Use Respiratory Protection

Response Statements

P301+P330+P331: If Swallowed: Rinse Mouth. Do NOT induce vomiting. Immediately call a poison center/physician

P303+P361+P353: If on Skin(or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Contact a poison center/physician if needed

P304+P 340+P312: If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: If in eyes: Rinses cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. Immediately call a poison center/doctor

Storage Statements

P403: Store in a well-ventilated place

P403+P233: Store in a well-ventilated place. Store in an appropriate container or containment

Disposal Statements

• Dispose of contents and containers in accordance with local, state, and federal Regulations

CAS #	Component	Percent
65997-15-1	Cement, Portland, Chemicals	90-95
13397-24-5	Gypsum	6-8
1317-65-3	Limestone	0-15
14808-60-7	Quartz	0-0.1

Section 3 - Composition/Information on Ingredients

Section 4 – First Aid Measures

4.1 First Aid:

First-aid measures after eye contact: Rinse eyes immediately with water for 15 minutes. Continue rinsing for several minutes to ensure particle removal. Get medical consultation immediately

First-aid measures after skin contact: Flush skin with water immediately. Remove contaminated clothing. Seek medical attention immediately.

First-aid measures after ingestion: Do not induce vomiting. Contact poison center/physician immediately

First-aid measures after inhalation: Remove victim to fresh air. Contact medical personnel immediately

4.2 Important Symptoms or Effects

Inhalation: Difficulty Breathing, Respiratory Irritation Skin Contact: Burns, Pain, Blisters Eye Contact: Burn, Pain, Discomfort, Severe Eye Damage Ingestion: Nausea, Vomiting

Section 5 – Firefighting Measures

Extinguishing Equipment: Suitable media to extinguish surrounding environment Hazardous Combustion Products: None
Fire Hazard: Product does not burn
Hazardous Decomposition or Byproducts: None spontaneously.
Firefighting Instructions: Wear appropriate firefighting equipment

Section 6 – Accidental Release Measures

General Measures: Use personal protective equipment outlined in Section VIII

Containment: Stop the spill in a safe manner

Clean-Up: Collect the material and place in containers. Ensure that dust generation is down to a minimum due to the hazards of the dust.

Environmental: Ensure product is quickly swept up to ensure cement does not go into waterways.

Section 7 – Handling and Storage

Handling Procedures:

Avoid skin and eye contact with the material or breathing the dust. Wear appropriate personal protective equipment as described in Section VIII. Wash thoroughly after exposure to product. Product is an engulfment hazard if stored in large enough container.

Storage Procedures:

Store in a cool, dry environment where only authorized personnel has access to.

Precautions to Be Taken for Handling and Storing:

Protect against physical damage. Store the material in a cool, dry well-ventilated location.

Section 8 – Exposure Control/Personal Protection

Control Parameters:

Cement, Portland, Chemicals (CAS # 65997-15-1)

- ACGIH(US): 1 mg/m³ TWA(respirable fraction)
- OSHA(US) PEL: 15 mg/m³ TWA(Total Dust), 5 mg/m³(respirable fraction)
- NIOSH(US): 10 mg/m³ TWA(Total Dust), 5 mg/m³(respirable fraction)

Limestone(CAS # 1317-65-3)

- ACGIH(US): 10 mg/m^3
- OSHA(US): 15 mg/m³ TWA (Total dust), 5 mg/m³ TWA(respirable fraction)

Gypsum(CAS #13397-24-5)

- OSHA(US) PEL: 15 mg/m³ TWA(Total Dust), 5 mg/m³(respirable fraction)
- NIOSH(US): 10 mg/m³ TWA(Total Dust), 5 mg/m³(respirable fraction)

Quartz(CAS # 14808-60-7)

- ACGIH(US) 0.025 mg/m³ TWA (Respirable Dust)
- *NIOSH(US): 0.05 mg/m³(respirable dust)*

Exposure Controls:

Engineering:

Provide exhaust or local ventilation or other engineering controls to keep the airborne concentrations of dust below their respective threshold limit value if needed.

Respiratory Protection (Specify Type):

Use local/general ventilation if possible. In situations with poor ventilation, use a NIOSH approved respirator or dust mask to protect against the inhalation of dust.

Protective Gloves:

Suitable Gloves

Eye Protection:

Use chemical safety glasses/goggles and/or a full face shield.

Other Protective Clothing or Equipment:

Wear impervious protective clothing, including boots, gloves, and coveralls, as appropriate, to prevent skin contact. Structural firefighters protective clothing will only provide limited protection.

Section 9 – Physical and Chemical Properties

Appearance: Solid, grey to white powder Upper Flammability: no data available Lower Flammability: No data available Odor: no observable odor Vapor Pressure: no data available Vapor Density: no data available pH: 12-14 Relative Density: no data available Melting Point: no data available Freezing Point: no data available Solubility: Slight Initial Boiling point: no data available Boiling Range: no data available Flash Point: no data available Evaporation Rate: no data available Flammability: not flammable Vapor Pressure: no data available Vapor Density: no data available Relative Density: no data available Solubility: no data available Partition Coefficient: no data available Auto ignition Temperature: no data available Decomposition Temperature: no data available Viscosity: no data available

Section 10 – Stability and Reactivity

10.1 Reactivity

No dangerous reactions should take place under intended use. Do not mix with other chemicals

10.2: Stability
Stable under normal dry storage conditions
10.3 Conditions to Avoid
Any unintended contact with water.
10.4 Incompatible Materials
None Known
10.5 Hazardous Decomposition Products
None Known

Section 11 – Toxicological information

Quartz(14808-60-7) LD50 oral rat=500 mg/kg IARC Group=1 NTP Status=2

Limestone(1317-65-3) LD50 Oral Rat=6450 mg/kg

Portland Cement(65997-15-1) IDLH=5000 mg/m³

Routes of Exposure: Skin and eye contact, inhalation, and ingestion.

Specific Target Organ Toxicity (single exposure): respiratory irritation Skin corrosion/irritation: Severe burns Eye Damage/Irritation: Serious eye damage Respiratory/Skin Irritation: allergic skin reaction, Respiratory tract irritation Carcinogenicity: Can cause cancer (Quartz)

Symptoms after contact related to exposure/toxicological characteristics

Skin Contact: Burns, irritation, blisters, rash, pain and discomfort

Eye Contact: Burn, eye damage, redness, excessive watering of eye

Ingestion: Nausea, Vomiting

Inhalation: Irritation of the respiratory tract

Section 12 – Ecological Information

12.1 Toxicity No information is available 12.2 Persistence and Degradability No data Available

12.3 Bio-accumulative potential No data available

12.4 Mobility in Soil No data available

12.5 Other Adverse Effects No data available

Section 13 – Disposal Considerations

13.1 Waste Treatment Methods

Disposal Recommendations: Dispose material in accordance with any applicable local, state, and Federal regulations

Section 15 – Regulatory Information

15.1 US Federal Regulations

Cement, Portland, chemicals (65997-15-1): Listed on US TSCA (Toxic Substance Control Act) Inventory

Limestone (1317-65-3): Listed on US TSCA (Toxic Substance Control Act) Inventory Quartz (14808-60-7): Listed on US TSCA (Toxic Substance Control Act) Inventory

15.2 State Regulations

State or Local Regulations: Product contains quartz or crystalline silica and trace amounts of other chemicals known to the State of California as causing cancer, birth defects, and/or reproductive harm

Quartz (14808-60-7)

California	California	California	California	No Significance
Proposition 65-	Proposition 65-	Proposition 65-	Proposition 65-	Risk
Carcinogens List	Developmental	Reproductive	Reproductive	Level(NSRL)
	Toxicity	Toxicity-Female	Toxicity Male	
Yes	No	No	No	No

Section 16 – Other information

SDS was prepared according to the Hazard Communication Standard (CFR 29 1910.1200) Prepared 4/27/2015