


Safety Data Sheet - Limestone

1. Identification

Product Identifier:	Limestone
Other Means of Identification:	Aggregate, Aglime, Calcium Carbonate, Coverstone, Limestone, Manufactured Sand, Mineral Filler, and Rip Rap.
Recommended Use:	Limestone is to be used in the manufacture of bricks, mortar, cement, concrete, plasters, paving materials, other construction materials, steel, consumer products, and other goods. Limestone aggregate may be distributed in bags, totes, and bulk shipments.
Recommended Restrictions:	None Known.
Manufacturer/Importer/Supplier/Distributor Information:	
Company:	L & W Quarries
Address:	112 W Maple Street; Centerville, IA 52544
Telephone:	641-437-4830
Emergency Phone Number:	641-437-4830

2. Hazard(s) Identification

GHS Classification:	Acute Toxicity Oral – Category 4 Carcinogenicity – Category 1A Specific Target Organ Toxicity Repeated Exposure – Category 2 Skin Corrosion/Irritation – Category 2B Eye Damage/Irritation – Category 2
GHS Label Elements:	

Signal Word:	Danger
Hazard Statement:	Harmful if swallowed. Causes skin and eye irritation. May cause cancer. May cause damage to organs (lung) through prolonged or repeated exposure.
Precautionary Statement:	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response:	If exposed or concerned: Get medical advice/attention
Storage:	Restrict or control access to stockpile areas. Engulfment hazard: To prevent burial or suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains aggregates without an effective procedure for assuring safety.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazards(s) not otherwise classified:	None known.
Supplemental information:	Respirable Crystalline Silica (RCS) may cause cancer. Limestone is a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). In its natural bulk state, limestone is not a known health hazard. Limestone may be subjected to various natural or mechanical forces that produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain industrial processes.

3. Composition/Information on Ingredients

Mixtures

Chemical name	CAS number	%
Calcium Carbonate	1317-65-3	> 50
Crystalline Silica (Quartz)	14808-60-7	> 0.1

4. First-Aid Measures

Inhalation:	Limestone dust: Move to fresh air. Call a physician if symptoms develop or persist.
Skin Contact:	Limestone dust: Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye Contact:	Limestone dust: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids apart. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Get medical attention if irritation develops or persists.
Ingestion:	Limestone dust: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.
Most important symptoms/effects:	Inhaling dust may cause discomfort in the chest, shortness of breath, and coughing.
Acute and Delayed:	Prolonged inhalation may cause chronic health effects. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica liberated from this product can cause silicosis, and may cause cancer.
Indication of immediate medical attention and special treatment needed:	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General Information:	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Pre-existing medical conditions that may be aggravated by exposure include disorders of the eye, skin and lung (including asthma and other breathing disorders). If addicted to tobacco, smoking will impair the ability of the lungs to clear themselves of dust.

5. Fire-fighting Measures

Suitable Extinguishing Media:	Limestone is not flammable. Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable Extinguishing Media:	None known.
Specific hazards arising from the chemical:	No unusual fire or explosion hazards noted. Not a combustible dust.
Special protective equipment and precautions for firefighters:	Use protective equipment appropriate for surrounding materials.
Fire-fighting equipment/instructions:	No specific precautions.
Specific Methods:	Contact with powerful oxidizing agents may cause fire and/or explosions (see section 10 of SDS)
General Fire Hazards:	No unusual fire or explosion hazards noted.

6. Accidental Release Measures

Personal precautions and emergency procedures:	Wear appropriate protective equipment and clothing during clean-up of materials that contain or may liberate limestone dust.
Methods and materials for containment and cleaning up:	Spilled material, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust. Do not dry sweep or use compressed air for clean-up.
Environmental Precautions:	Avoid discharge of fine particulate matter into drains or water courses.

7. Handling and Storage

Handling and Storage:

Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid dust formation or accumulation.

Conditions for safe storage:

Avoid dust or accumulation.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits:

- 1 - Value equivalent to OSHA formulas (29 CFR 1910.1000; 29 CFR 1917; 29 CFR 1918)
- 2 - Value also applies to MSHA Metal/Non-Metal (1973 TLVs at 30 CFR 56/57.5001).
- 3 - OSHA enforces 0.250 mg/m³ in construction and shipyards (CPL-03-00-007).
- 4 - Value also applies to OSHA construction (29 CFR 1926.55 Appendix A) and shipyards (29 CFR 1915.1000, Table Z).
- 5 - MSHA limit = 10 mg/m³.

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Particulates not otherwise classified (CAS SEQ250).	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction Total dust (4)
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (4) Total dust (5)

U.S. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m ³ 0.1 mg/m ³	Total dust (1,2) Respirable (1,2,3)
Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	TWA	0.15 mg/m ³ 0.05 mg/m ³	Total dust (1) Respirable (1,2)
Particulates not otherwise classified (CAS SEQ250)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (1) Total dust (1,4,5)

US. ACGIH Threshold Limit Values®

Components	Type	Value	Form
Crystalline Silica (all forms; CAS mixture)	TWA	0.025 mg/m ³	Respirable fraction
Particulates not otherwise classified silica) (CAS Mixture)	TWA	3 mg/m ³ 10 mg/m ³	Respirable particles (2) Inhalable particles (2)

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline Silica (all forms; CAS mixture)	TWA	0.05 mg/m ³	Respirable dust
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³ 10 mg/m ³	Respirable fraction Total dust

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Exposure Guidelines: OSHA PELs, MSHA PELs, and ACGIH TLVs are 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10-hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including "Particulates Not Otherwise Classified," "Particulates Not Otherwise Regulated," "Particulates Not Otherwise Specified," and "Inert or Nuisance Dust" are often used interchangeably; however, the user should review each agency's terminology for differences in meanings.

Appropriate Engineering Controls: Good general ventilation (typically 10 air changes per hour indoors) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Wear safety glasses with side shields (or goggles)
Hand Protection: Use personal protective equipment as required.
Respiratory Protection: When handling or performing work with limestone that produces dust or respirable crystalline silica in excess of applicable exposure limits, wear a NIOSH-approved respirator that is properly fitted and is in good condition. Respirator must be used in accordance with all applicable workplace regulations.

Thermal Hazards: Not anticipated. Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance
Physical State: Solid.
Form: Solid, particles.
Color: White granular
Odor: Not applicable.
pH: 7-9 (in water)
Melting Point: Not applicable.
Boiling Point: Not applicable.
Flash Point: Non-combustible.
Evaporation Rate: Not applicable.
Upper & Lower Flammability: Not applicable
Vapor Pressure: Not applicable.
Vapor Density: Not applicable.
Solubility (water): Insoluble.
Auto Ignition Temperature: Not applicable.
Viscosity: Not applicable.

10. Stability and Reactivity

Reactivity: The product is stable and on-reactive under normal conditions of use, storage, and transport.
Chemical Stability: Material is stable under normal conditions.
Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

11. Toxicological Information

Information on Likely Routes of Exposure

Inhalation:

Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects including lung and kidney cancer.

Skin Contact:

Limestone dust: May cause irritation through mechanical abrasion.

Eye Contact:

Limestone dust: May cause irritation through mechanical abrasion.

Ingestion:

Not likely, due to the form of the product. However, accidental ingestion of the content may cause discomfort.

Physical, Chemical, and Toxicological Characteristics:

Limestone dust: Discomfort in the chest. Shortness of breath. Coughing.

Information on Toxicological Effects

Acute Toxicity:

Not expected to be acutely toxic.

Skin Corrosion/Irritation:

This product is not expected to be a skin hazard.

Serious Eye Damage/Eye Irritation:

Direct contact with eyes may cause temporary irritation.

Respiratory Sensitization:

None known.

Skin Sensitization:

Not known to be a dermal irritant or sensitizer.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen, and classified by ACGIH as a suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Respirable Tridymite and Cristobalite 1 Carcinogenic to humans.

(Other forms of Crystalline) (CAS Mixture)

NTP Report on Carcinogens

Crystalline Silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not Listed.

Reproductive Toxicity:

Not expected to be a reproductive hazard. Not classified.

Specific Target Organ Toxicity

Single Exposure:

Not Classified.

Specific Target Organ Toxicity

Repeated Exposure:

Respirable crystalline silica: May cause damage to organs (lung) through prolonged or repeated exposure.

Aspiration Hazard:

Due to the physical form of the product it is not an aspiration hazard.

Chronic Effects:

Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

12. Ecological Information

Ecotoxicity:

Not expected to be harmful to aquatic organisms. Discharging limestone dust and fines into waters may increase total suspended particulate (TSP) levels that can be harmful to certain aquatic organisms.

Persistence and Degradability:

Not applicable.

Bioaccumulative Potential:

Not applicable.

Mobility in Soil:

Not applicable.

Other Adverse Effects:

No other adverse effects are expected from this component.

13. Disposal Considerations

Disposal Instructions:	Do not allow fine particulate matter to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with fine particulates. Dispose contents in accordance with local/regional/national regulations.
Hazardous Waste Code:	Not regulated.
Waste from Residues/Unused Products:	Dispose of in accordance with local regulations. Empty containers or lines may retain some product residues. This material and its containers must be disposed of in a safe manner. (See Disposal Instructions).
Contaminated Packaging:	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty packaging materials should be recycled or disposed of in accordance with applicable regulations and practices.

14. Transport Information

DOT:	Not regulated as dangerous goods.
IATA:	Not regulated as dangerous goods.
IMDG:	Not regulated as dangerous goods.
Transport in bulk according to Annex II Of MARPOL 73/78 and the IBC Code:	Not applicable.

15. Regulatory Information

US Federal Regulations:	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TCSA Section 12(b) Export Notification (40 CFR 707, Subpart D)	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazardous substance	Not listed.
SARA 311/312 Hazardous chemical	Yes.
SARA 313 (TRI reporting)	Not regulated.
Other federal regulations	
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not regulated.
Safe Drinking Water Act (SDWA)	Not Regulated
US state regulations	
US. Massachusetts RTK - Substance List	
Crystalline Silica (Quartz) (CAS 14808-60-7)	
Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	
US. New Jersey Worker and Community Right-to-Know Act	
Crystalline Silica (Quartz) (CAS 14808-60-7)	
Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	
US. Pennsylvania Worker and Community Right-to-Know Law	
Crystalline Silica (Quartz) (CAS 14808-60-7)	
Respirable Tridymite and Gristobalite (other forms of crystalline silica) (GAS Mixture)	

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline Silica (Quartz) (GAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On Inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information, Including Date of Preparation or Last Revision

Issue Date: 05/29/2015
Revision Date: 05/29/2015
Version Date: 05/29/2015

Hazardous Material Information System (HMIS):	Health			1
	Flammability			0
	Physical Hazard			0
	Personal Protection			B

NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

Protective Equipment: Safety glasses, gloves

Disclaimer:

This SDS provides information on various types of limestone. The information provided herein is believed by L & W Quarries to be accurate at the time of preparation or prepared from sources believed to be reliable. Health and safety precautions in this data sheet may not be adequate for all individuals or situations. Users have the responsibility to comply with all laws and procedures applicable to the safe handling and use of the products, to determine the suitability of the product for its intended use, and to understand possible hazards associated with using limestone.

L & W QUARRIES MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREFOR ANY PURPOSE OR CONCERNING THE ACCURACY OF INFORMATION PROVIDED.