

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29

Page: 1/9

Version: 3.0

(30606142/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: No data available.

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic

**Label elements**

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29

Page: 2/9

Version: 3.0

(30606142/SDS\_GEN\_US/EN)

Pictogram:



Signal Word:

Warning

Hazard Statement:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (on hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

No applicable information available.

**According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

### Emergency overview

WARNING:

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Ingestion may cause irritation to mucous membranes.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

Keep container tightly closed.

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29  
Version: 3.0

Page: 3/9  
(30606142/SDS\_GEN\_US/EN)

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25068-38-6	>= 75.0 - <= 100.0 %	bisphenol A-epichlorohydrin resin
68609-97-2	>= 10.0 - < 15.0 %	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25068-38-6	60.0 - 100.0 %	bisphenol A-epichlorohydrin resin
68609-97-2	7.0 - 13.0 %	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

##### If on skin:

Wash thoroughly with soap and water.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

### 5. Fire-Fighting Measures

#### Extinguishing media

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29  
Version: 3.0

Page: 4/9  
(30606142/SDS\_GEN\_US/EN)

---

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.  
For large amounts: Pump off product.

---

## 7. Handling and Storage

### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

### Protection against fire and explosion:

The substance/product is non-combustible. The product does not contribute to the spreading of flames, nor is it self combustible, not explosive. Take precautionary measures against static discharges.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep in a cool place. Keep container tightly closed. Store in an approved area.

Protect from temperatures below: 5 °C

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29

Page: 5/9

Version: 3.0

(30606142/SDS\_GEN\_US/EN)

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 40 °F

The packed product must be protected from temperatures below the indicated one.

### 8. Exposure Controls/Personal Protection

#### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

#### Personal protective equipment

##### Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Wear a NIOSH-certified (or equivalent) organic vapour respirator.

##### Hand protection:

Wear chemical resistant protective gloves.

##### Eye protection:

Safety glasses with side-shields.

##### Body protection:

Impermeable protective clothing

##### General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

### 9. Physical and Chemical Properties

Form:	liquid	
Odour:	odourless	
Odour threshold:		No applicable information available.
Colour:	clear	
pH value:		not applicable
Melting point:		No applicable information available.
Boiling point:	> 200 °C	
Sublimation point:		No applicable information available.
Flash point:	> 93.34 °C	(calculated)
Flammability:	not determined	
Lower explosion limit:		No applicable information available.
Upper explosion limit:		No applicable information available.
Autoignition:		not applicable Literature data.
Vapour pressure:	< 1 mmHg	( 25 °C)
Density:	1.1324 g/cm <sup>3</sup> 9.34 lb/USg	( 25 °C)
Relative density:		No applicable information available.
Bulk density:		not applicable
Vapour density:		No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Thermal decomposition:		No applicable information available.

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29

Page: 6/9

Version: 3.0

(30606142/SDS\_GEN\_US/EN)

Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

### 10. Stability and Reactivity

#### Reactivity

No applicable information available.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

#### Chemical stability

No applicable information available.

#### Possibility of hazardous reactions

No applicable information available.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

No applicable information available.

#### Hazardous decomposition products

Decomposition products:

No applicable information available.

Thermal decomposition:

No applicable information available.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

##### Oral

No applicable information available.

##### Dermal

No applicable information available.

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29  
Version: 3.0

Page: 7/9  
(30606142/SDS\_GEN\_US/EN)

---

### Assessment other acute effects

No applicable information available.

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

*Information on: Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.*

*Assessment of irritating effects: Skin contact causes slight irritation.*

*Information on: bisphenol A-epichlorohydrin resin*

*Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.*

-----

### Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

*Information on: bisphenol A-epichlorohydrin resin*

*Assessment of sensitization:*

*Sensitization after skin contact possible.*

-----

Can sensitize the skin and/or respiratory tract of allergic persons. May produce an allergic reaction.

## Chronic Toxicity/Effects

### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

## Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

The product has not been tested.

### Additional information

Other ecotoxicological advice:

Ecological data are not available.

---

## 13. Disposal considerations

### Waste disposal of substance:

Incinerate or dispose of in a licensed facility. Observe all local regulations.

# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29  
Version: 3.0

Page: 8/9  
(30606142/SDS\_GEN\_US/EN)

---

### 14. Transport Information

**Land transport**  
USDOT

Not classified as a dangerous good under transport regulations

**Sea transport**  
IMDG

Not classified as a dangerous good under transport regulations

**Air transport**  
IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

#### Federal Regulations

**Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Not hazardous;

**HMIS III rating**

Health: 2 Flammability: 1 Physical hazard: 0

---

### 16. Other Information

**SDS Prepared by:**

BASF NA Product Regulations  
SDS Prepared on: 2014/04/29

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING



# Safety Data Sheet

## MasterSeal 350 PART A also TrafficGuard EP 35 PTA

Revision date : 2014/04/29

Page: 9/9

Version: 3.0

(30606142/SDS\_GEN\_US/EN)

---

WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET