

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29

Page: 1/11

Version: 2.0

(30605578/SDS\_GEN\_US/EN)

### 1. Identification

Product identifier used on the label

## MasterKure CC 250SB also KURE N SEAL 25LV

### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

### Details of the supplier of the safety data sheet

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

### Other means of identification

Chemical family: No data available.

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

Flam. Liq.	3	Flammable liquid
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Muta.	1B	Germ cell mutagenicity
Carc.	1B	Carcinogenicity
Repr.	2 (fertility)	Reproductive toxicity
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 2/11  
(30605578/SDS\_GEN\_US/EN)

STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
STOT RE	1	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility.
H350	May cause cancer.
H340	May cause genetic defects.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P243	Take precautionary measures against static discharge.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.

Precautionary Statements (Response):

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29

Page: 3/11

Version: 2.0

(30605578/SDS\_GEN\_US/EN)

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P303 + P352	IF ON SKIN (on hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P391	Collect spillage.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

### Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

### Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

### According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

### Emergency overview

#### WARNING:

COMBUSTIBLE LIQUID AND VAPOR.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Keep container tightly closed.

Avoid all sources of ignition: heat, sparks, open flame.

## 3. Composition / Information on Ingredients

### According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8052-41-3	>= 20.0 - < 50.0 %	Stoddard solvent
64742-95-6	>= 20.0 - < 25.0 %	solvent naphtha
95-63-6	>= 15.0 - < 20.0 %	1,2,4-trimethylbenzene
64742-82-1	>= 7.0 - < 15.0 %	Naphtha (petroleum), hydrodesulfurized heavy
108-67-8	>= 1.0 - < 3.0 %	mesitylene

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29

Page: 4/11

Version: 2.0

(30605578/SDS\_GEN\_US/EN)

1330-20-7	>= 0.3 - < 3.0 %	Xylene
25340-17-4	>= 0.3 - < 1.0 %	Benzene, diethyl-
25550-14-5	>= 0.3 - < 3.0 %	ethyltoluene
91-20-3	>= 0.1 - < 1.0 %	naphthalene

### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8052-41-3	>= 10.0 - <= 30.0 %	Stoddard solvent
64742-95-6	>= 10.0 - <= 30.0 %	solvent naphtha
95-63-6	>= 10.0 - <= 30.0 %	1,2,4-trimethylbenzene
64742-82-1	>= 5.0 - <= 10.0 %	Naphtha (petroleum), hydrodesulfurized heavy
108-67-8	>= 1.0 - <= 5.0 %	mesitylene
1330-20-7	>= 1.0 - <= 5.0 %	Xylene
100-41-4	>= 0.1 - <= 1.0 %	ethylbenzene
91-20-3	>= 0.1 - <= 1.0 %	naphthalene

The product contains:

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25551-13-7	>= 1.0 - < 3.0 %	Benzene, trimethyl-

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

#### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 5/11  
(30605578/SDS\_GEN\_US/EN)

known specific antidote.

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

#### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

#### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

#### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.  
For large amounts: Pump off product.

---

### 7. Handling and Storage

#### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

#### Conditions for safe storage, including any incompatibilities

No applicable information available.

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 6/11  
(30605578/SDS\_GEN\_US/EN)

Suitable materials for containers: High density polyethylene (HDPE)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 5 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 40 °F

The packed product must be protected from temperatures below the indicated one.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

naphthalene	OSHA PEL ACGIH TLV	PEL 10 ppm 50 mg/m <sup>3</sup> ; TWA value 10 ppm ; STEL value 15 ppm ; Skin Designation ; The substance can be absorbed through the skin.
1,2,4-trimethylbenzene	ACGIH TLV	TWA value 25 ppm ;
mesitylene	ACGIH TLV	TWA value 25 ppm ;
Xylene	OSHA PEL ACGIH TLV	PEL 100 ppm 435 mg/m <sup>3</sup> ; TWA value 100 ppm ; STEL value 150 ppm ;
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m <sup>3</sup> ; TWA value 100 ppm ;
Benzene, trimethyl-	ACGIH TLV	TWA value 25 ppm ;
Naphtha (petroleum), hydrodesulfurized heavy	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m <sup>3</sup> ; TWA value 100 ppm ;

#### **Advice on system design:**

No applicable information available.

#### Personal protective equipment

##### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

##### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

##### **Eye protection:**

Tightly fitting safety goggles (chemical goggles).

##### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29

Page: 7/11

Version: 2.0

(30605578/SDS\_GEN\_US/EN)

### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:		No applicable information available.
Colour:	clear	
pH value:		The product has not been tested.
Melting point:		No applicable information available.
Boiling point:	137.22 - 171.11 °C	
Sublimation temperature:		No applicable information available.
Flash point:	109 °F	
Flammability:	not determined	
Lower explosion limit:	0.9 %(V)	
Upper explosion limit:	7.0 %(V)	
Vapour pressure:		The product has not been tested.
Density:	0.9046 g/cm3	( 20 °C)
Relative density:		No applicable information available.
Bulk density:		not applicable
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Viscosity, dynamic:		No applicable information available.
Viscosity, kinematic:	37 mm2/s	( 40 °C)
Solubility in water:		insoluble
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

See MSDS section 7 - Handling and storage.

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 8/11  
(30605578/SDS\_GEN\_US/EN)

---

### Incompatible materials

oxidizing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: No applicable information available.

#### Oral

No applicable information available.

#### Inhalation

No applicable information available.

#### Dermal

No applicable information available.

#### Assessment other acute effects

Assessment of STOT single:

A single exposure may have relevant toxic effects on organs. Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

#### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

#### Sensitization

Assessment of sensitization: No applicable information available.

#### Aspiration Hazard

Aspiration hazard May be harmful if swallowed and enters airways.

### Chronic Toxicity/Effects

#### Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.

#### Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

### Symptoms of Exposure



# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 9/11  
(30605578/SDS\_GEN\_US/EN)

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity  
Assessment of aquatic toxicity:  
Acutely toxic for aquatic organisms.

### Additional information

Other ecotoxicological advice:  
May cause long-term adverse effects in the aquatic environment.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### Land transport

USDOT

Hazard class:	C
Packing group:	III
ID number:	UN 1263
Hazard label:	CBL
Proper shipping name:	PAINT, COMBUSTIBLE LIQUID

Classified as combustible liquid in containers greater than 119 gallons.

### Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT

### Air transport

IATA/ICAO

Hazard class:	3
---------------	---

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29  
Version: 2.0

Page: 10/11  
(30605578/SDS\_GEN\_US/EN)

Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

### 15. Regulatory Information

#### Federal Regulations

##### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Acute; Chronic; Fire

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	98-82-8	cumene
1000 LBS	100-41-4; 108-88-3	ethylbenzene; Toluene
100 LBS	1330-20-7; 91-20-3	Xylene; naphthalene
10 LBS	71-43-2	Benzene

#### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	8052-41-3	Stoddard solvent
MA, NJ, PA	95-63-6	1,2,4-trimethylbenzene
MA, NJ, PA	64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
MA, NJ, PA	108-67-8	mesitylene
MA, NJ, PA	1330-20-7	Xylene
MA, NJ, PA	100-41-4	ethylbenzene
MA, NJ, PA	91-20-3	naphthalene

##### CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

##### NFPA Hazard codes:

Health : 2 Fire: 2 Reactivity: 0 Special:

##### HMIS III rating

Health: 2<sup>+</sup> Flammability: 2 Physical hazard: 0

### 16. Other Information

##### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2014/05/29

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring

# Safety Data Sheet

## MasterKure CC 250SB also KURE N SEAL 25LV

Revision date : 2014/05/29

Page: 11/11

Version: 2.0

(30605578/SDS\_GEN\_US/EN)

---

the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET